



S8L72-11

**Dual Voice Coil
Subwoofer 20 cm**

**Power Handling
450 Watts RMS / 900 Watts Max.**

Technical Specifications

Impedance	Zn	2 x 2 Ohms
Voice Coil Diameter	Ø	50 mm
Max. Linear Excursion	Xmax	+/- 12 mm
Cone Area	Sd	273 cm ²
Moving Mass	Mms	110,5 g
DC Resistance	Re	2 x 1,8 Ohms
Resonance Frequency	Fs	41,9 Hz
Mechanical Q-Factor	Qms	6,99
Electrical Q-Factor	Qes	0,63
Total Q-Factor	Qts	0,57
Equivalent Air Volume	VAS	9,8 L
Flux Density	B/L	12,757 N/A
Efficiency 1W/1m	SPL	82,5 dB

Recommended Enclosure

Ported Box	
Vented Volume:	22,6 L
Port Area:	107 cm ²
Port Length:	50 cm

Recommended Enclosure

Ported Box	
Vented Volume:	18,7 L
Port Area:	91 cm ²
Port Length:	49 cm

Mechanical Components

- Diecast Aluminium Basket
- Polypropylene Cone
- Santoprene Surround
- Polypropylene Dustcap
- Single Spider
- Single Magnet
- Polyimide Voice Coil Former

Dimensions & Weight

External Diameter:	224 mm
Mounting Diameter:	184 mm
Mounting Depth:	121 mm
Shipping Weight:	6,8 kg

